

## AC charging wallbox

The Prime Series wallbox is the entry-level EVtrip family of ev charging systems. It features a compact thermoplastic housing certified to IP65 IK09 and is available with 5m cable and Type 2 interlocked socket with shutter. The control system allows remote control, charging power modulation, photovoltaic charging management and much other. It's available in the single-phase (max 7.4 kW) or three-phase (max 22kW) version also with the charging through photovoltaic surplus.

## Technical specifications

Mechanical resistance	IP65 / IK09
Housing material	PC
Operating temperature	From -25°C to +45°C
Storage temperature	From -40°C to +60°C
Operating humidity	5% to 95% non-condensing
Signalling	RGB colour indicator
Meters	MID certified
Enabling payments	On request
Network connection	IoT GSM / WiFi / Bluetooth
Weight	4 kg
Pedestal	On request



# PRIME

## Single-phase models (7,4kW)

<b>Model</b>	<b>WB Prime Smart T2C</b>
<b>Code</b>	<b>40125</b>
Dimensions	205 x 255 x 112 mm
Input Voltage	230 VAC 50/60 Hz
<b>Max. current/power</b>	<b>32 A / 7,4 kw</b>
Stand-by consumption	1,8 W
Recharge	Mode 3 acc. IEC 61851
AC output voltage	230 VAC (1P + N + PE)
Output	1 x Cable 5 m Type 2
Leakage current circuit >6mA	On request
Electrical protections	Not included
Operation	Plug&Charge
Output power adjustment	Via app
Power modulation according to home consumption	On request (through delivered toroid)
User profile management	On request
Payment management	On request
Charging with photovoltaic surplus	No